

FL 210A

Horizontal and vertical lasers for interior and exterior applications.

Two new models with improved selflevelling, rotational accuracy and improved technical construction.

Instant self-levelling makes these lasers ideal when applications necessitate frequent positional changes.



- Instant self-levelling
- Horizontal self-levelling with automatic shut-off and audible alarm when out of tolerance
- Easy vertical set-up with one foot screw
- Variable rotating speed
- Scanning and laser dot mode
- Permanent 90° beam to zenith
- NiMH batteries
- Can be used with alkaline batteries
- Dust/water protection IP 66

TECHNICAL DATA

Self-levelling range	± 3,5°
Laser diode	red
Accuracy horizontal	± 1 mm / 10 m
Accuracy vertical	± 1,5 mm / 10 m
Working range with receiver	Ø 400 m
Rotating speed	150, 200, 250, 300 rpm
Laser class	2
Scan angle	0°, 20°, 40°
Temperature range	-10 °C - +45 °C
Dust/water protection	IP 66
Dimensions	180 x 162 x 202 mm
Weight incl. all accessories	5,7 kg
Power supply	4 x C NiMH*
 	
 *	with 6,4 V intelligent charger,

alkaline batteries can be used alternatively

SUPPLIED WITH

Receiver FR 45 with clamp, Remote control, Rechargeable batteries / Charger, Floor / wall mount, Magnetic target, Laser glasses, Carrying case