

FLG 260VA Green

Fully automatic horizontal and vertical laser for internal applications. Similar functions to the FL 260VA but incorporating a green laser diode for improved visibility under difficult measuring conditions such as bright surroundings and long distances.



- Visible laser beam
- Adjusted slope setting (manual) up to $\pm 5^\circ$ ($\pm 9\%$) in X and Y axis
- Single slope setting up to $\pm 5^\circ$ ($\pm 9\%$)
- 2 Rotating speeds
- Variable scanning and laser point mode
- Permanent 90° beam to zenith
- V-W-S function combined with TILT function
- Automatic TILT function
- Remote control screen
- NiMH batteries
- Can be used with alkaline batteries
- Li-Ion battery technology
- Intelligent charger
- Dust/water protection IP 66

TECHNICAL DATA

Self-levelling range	5°
Laser diode	green
Accuracy horizontal	$\pm 0,5 \text{ mm} / 10 \text{ m}$
Accuracy vertical	$\pm 1,0 \text{ mm} / 10 \text{ m}$
Working range with receiver	$\varnothing 400 \text{ m}$
Rotating speed	800, 300 rpm
Laser class	3R
Scan angle	0°, 10°, 45°, 90°, 180°
Manual slope setting X and Y axis	$\pm 5^\circ$ ($\pm 9\%$)
Single slope	
Temperature range	0 °C - +40 °C
Dimensions	219 x 160 x 202 mm
Weight	2,6 kg
Dust/water protection	IP 66
Automatic tilt function	yes
V-W-S function	yes
Power supply	6,4 V*
 	
 	

* with 6,4 V intelligent charger, battery



SUPPLIED WITH

Remote control, Rechargeable batteries, Charger, Floor mount, Magnetic target, Laser glasses, Carrying case