

FL 260VA

Fully automatic horizontal and vertical laser. Compact ergonomic design and intuitive operation.
A multi-functional laser for interior and exterior applications.



- Visible laser beam
- Adjusted slope setting (manual) up to $\pm 5^\circ$ ($\pm 9\%$) in X and Y axis
- Single slope setting up to $\pm 5^\circ$ ($\pm 9\%$)
- 2 Rotating speeds
- Variable scanning and laser point mode
- Permanent 90° beam to zenith
- V-W-S function combined with TILT function
- Automatic TILT function
- Remote control screen
- NiMH batteries
- Can be used with alkaline batteries
- Li-Ion battery technology
- Intelligent charger
- Dust/water protection IP 66

TECHNICAL DATA

Self-levelling range	5°
Laser diode	red (HP version)
Accuracy horizontal	$\pm 0,5$ mm / 10 m
Accuracy vertical	$\pm 1,0$ mm / 10 m
Working range with receiver	\varnothing 600 m
Rotating speed	800, 300 rpm
Laser class	3R
Scan angle	0°, 10°, 45°, 90°, 180°
Manual slope setting X and Y axis	$\pm 5^\circ$ ($\pm 9\%$)
Single slope	One axis tilted, other axis self-levelled
Temperature range	-10 °C - +45 °C
Dimensions	219 x 160 x 202 mm
Weight	2,6 kg
Dust/water protection	IP 66
Automatic tilt function	yes
V-W-S function	yes
Power supply	6,4 V*
	
	
	* with 6,4 V intelligent charger, battery



SUPPLIED WITH

Receiver FR 45 with clamp, Remote control, Rechargeable batterie / Charger, Floor mount, Magnetic target, Laser glasses, Carrying case